



LUBRICANTS™

POWER TO PERFORM™

HYLUBE MILCY 30, 40, 50

DESCRIPTION

HYLUBE MILCY 30,40,50 are superior quality, monograde heavy diesel engine oils developed for naturally artirated diesel engines. The product is made from paraffinic base stocks and fortified with selected additives to deliver satisfactory performance.

MEETS REQUIREMENTS OF

- API CF/SF
- MIL-L-2104C
- E-DL 3 of BIS 13656:2014
- MACK T-8A

APPLICATIONS

Recommended for heavy commercial vehicles, light commercial vehicles,tractors, diesel passenger cars and jeeps requiring monograde oils.

FEATURES & BENEFITS

- Extended TBN reserves
- Prevents oil thickening and enhances oil life
- Control of corrosive wear
- Exceptional thermal & oxidation stability
- Prolonged engine life & enhanced drain period
- Outstanding engine cleanliness

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

HYLUBE MILCY	30	40	50
Kinematic Viscosity, @ 100°C, cSt	10.3-11.5	13.5-15.2	17.5-24
Viscosity Index	108	111	99
Flash Point, (COC) °C	230	230	230
Pour Point, °C	-21	-15	-9
TBN, mg KOH/g	10.4	10.2	11.5